

SAFETY DATA SHEET

OX Engineered Products LLC, Charleston, Illinois
 1255 North 5th Street
 Charleston, IL 61920
 800-345-8881

Prepared 9/20/2018



| SECTION 1 | IDENTIFICATION |
|---|--|
| Product Name: | SI-Strong 0.50 and 1.0 inch Structural Insulated Sheathing |
| Type of Product: | Construction material |
| <p>This product is not a hazardous chemical as defined by the Occupational Safety and Health Administration (OSHA), 29 CFR 1910.1200 as this product meets the definition of an article and is exempted from the SDS requirement as defined by Section 1.3.2.1.1 of the Globally Harmonized System (GHS), and Section 3 of the Canadian Hazardous Products Act. Therefore, the information provided in this Safety Data Sheet (SDS) is for informational purposes only and does not necessarily reflect warning and precautionary statements indicated in the product's packaging or container label.</p> | |

| SECTION 2 | HAZARD(S) IDENTIFICATION |
|----------------------------------|---|
| Classifications: | None |
| Pictograms: | None Required |
| Signal Word: | None Required |
| Hazard Statements: | None Required |
| Precautionary Statements: | <p>Solid or dust may cause irritation or corneal injury due to mechanical action. Safety glasses are recommended to be worn for fabrication operations. If in the eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical attention.</p> <p>Fabrication methods which involve cutting into this product may release the blowing agent(s) remaining in the cells. Provide adequate ventilation to ensure airborne concentrations of the agents are below exposure limits. This board is combustible and should not be exposed to flame or other ignition sources.</p> |

| SECTION 3 | COMPOSITION/INFORMATION ON INGREDIENTS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|-----------------------------|-----------------------------|-----------|-----------|-------|--|----------------|-------|----------|-----------|------|------------------------------|-------------|------|-------------|----------------|------|---------------------|-----------|------|-----------------------------|------------|------|---------------|-----------|------|------------------------------------|------------|------|--|
| <p>Components of construction: Paper, polymer and glue.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Component</th> <th>CAS Registry No.</th> <th>% by Weight (Approximately)</th> </tr> </thead> <tbody> <tr> <td>Cellulose</td> <td>9004-34-6</td> <td>> 70%</td> </tr> <tr> <td>Modified Polyisocyanurate Rigid Cellular polymer</td> <td>None available</td> <td>< 15%</td> </tr> <tr> <td>Aluminum</td> <td>7429-90-5</td> <td>< 5%</td> </tr> <tr> <td>Hydrocarbon blowing agent(s)</td> <td>Proprietary</td> <td>< 5%</td> </tr> <tr> <td>Kraft Paper</td> <td>None available</td> <td>< 5%</td> </tr> <tr> <td>Ethene, homopolymer</td> <td>9002-88-4</td> <td>< 5%</td> </tr> <tr> <td>Vinyl alcohol acetate resin</td> <td>25213-24-5</td> <td>< 5%</td> </tr> <tr> <td>Sulfamic Acid</td> <td>5329-14-6</td> <td>< 1%</td> </tr> <tr> <td>Tris (1-chloro-2-propyl) phosphate</td> <td>13674-84-5</td> <td>< 1%</td> </tr> </tbody> </table> | Component | CAS Registry No. | % by Weight (Approximately) | Cellulose | 9004-34-6 | > 70% | Modified Polyisocyanurate Rigid Cellular polymer | None available | < 15% | Aluminum | 7429-90-5 | < 5% | Hydrocarbon blowing agent(s) | Proprietary | < 5% | Kraft Paper | None available | < 5% | Ethene, homopolymer | 9002-88-4 | < 5% | Vinyl alcohol acetate resin | 25213-24-5 | < 5% | Sulfamic Acid | 5329-14-6 | < 1% | Tris (1-chloro-2-propyl) phosphate | 13674-84-5 | < 1% | |
| Component | CAS Registry No. | % by Weight (Approximately) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cellulose | 9004-34-6 | > 70% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Modified Polyisocyanurate Rigid Cellular polymer | None available | < 15% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Aluminum | 7429-90-5 | < 5% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Hydrocarbon blowing agent(s) | Proprietary | < 5% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Kraft Paper | None available | < 5% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ethene, homopolymer | 9002-88-4 | < 5% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Vinyl alcohol acetate resin | 25213-24-5 | < 5% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Sulfamic Acid | 5329-14-6 | < 1% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Tris (1-chloro-2-propyl) phosphate | 13674-84-5 | < 1% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>< Less than > Greater than CAS Chemical Abstract Service</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

SAFETY DATA SHEET

OX Engineered Products LLC, Charleston, Illinois
1255 North 5th Street
Charleston, IL 61920
800-345-8881

Prepared 9/20/2018



| SECTION 4 | FIRST AID MEASURES |
|--|--------------------|
| INHALATION: Repeated exposures to dusts of this material are not anticipated to result in systemic toxicity or permanent lung injury; however, excessive exposures may cause less severe respiratory effects. If excessive inhalation of dust occurs, remove to fresh air. Dust in throat and nasal passages should clear spontaneously. Get prompt medical attention if breathing remains difficult or if irritation persists. | |
| EYES: If dusts generated from fabrication operations get into the eyes, immediately flush eye(s) with plenty of clean potable water for at least 15 minutes while holding eyelids open. Beyond flushing, do not attempt to remove material from the eye(s). Get medical attention if irritation or pain persist or develop later. | |
| SKIN: None expected during normal handling. Mechanical injury only. Skin absorption is unlikely due to this product being an article. | |
| INGESTION: Very low toxicity if swallowed. May cause choking if swallowed. May cause gastrointestinal blockage if swallowed. Do not give laxatives. Do not induce vomiting unless directed by medical personnel | |

| SECTION 5 | FIRE-FIGHTING MEASURES |
|--|------------------------|
| EXTINGUISHING AGENT: Water spray, carbon dioxide, and dry chemical. | |
| UNUSUAL FIRE AND EXPLOSION HAZARDS: Mechanical cutting, grinding, or sawing can cause formation of dusts. To reduce the potential for dust explosion, do not permit dust to accumulate to an average of 1/32 inch (0.88 mm) thick (about the diameter of a paper clip wire). This product contains a flame retardant to inhibit accidental ignition from small fire sources. The plastic foam product is combustible and should be protected from flames and other high heat sources. Dense smoke is emitted when burned without sufficient oxygen. | |
| SPECIAL FIRE FIGHTING PROCEDURES: Wear a National Institute for Occupational Safety and Health (NIOSH) approved positive pressure Self-Contained Breathing Apparatus (SCBA) and fully protective clothing (such as turnout gear) as necessary. | |
| HAZARDOUS COMBUSTION PRODUCTS: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. In smoldering or flaming conditions, carbon monoxide, carbon dioxide, and carbon are generated. Combustion products may include but not limited to nitrogen oxides. Combustion products may also include trace amounts of hydrogen halides. | |

| SECTION 6 | ACCIDENTAL RELEASE MEASURES |
|--|-----------------------------|
| If board is broken, crushed, or similar, clean up and contain. Prevent debris from entering storm water drains, sewers, etc. | |

| SECTION 7 | HANDLING AND STORAGE |
|---|----------------------|
| General Handling: This material is combustible and should not be exposed to flame or other ignition sources. No smoking, open flames, or sources of ignition in handling and storage area(s). Fabrication methods which involve cutting into this product may release the blowing agent(s) remaining in the cells. Good housekeeping and controlling of dusts are recommended for safe handling. | |

SAFETY DATA SHEET

OX Engineered Products LLC, Charleston, Illinois
 1255 North 5th Street
 Charleston, IL 61920
 800-345-8881 Prepared 9/20/2018



| | |
|------------------|--|
| SECTION 8 | EXPOSURE CONTROLS/PERSONAL PROTECTION |
|------------------|--|

| Component | OSHA PEL | ACGIH TLV-TWA/TLV-STEL |
|--|---|------------------------|
| Aluminum metal and insoluble compounds | 15 mg/m ³ | 1 mg/m ³ |
| Continuous filament glass fiber | (as particulates – 15 mg/m ³) | 5 mg/m ³ |
| Isopentane | None established | None established |
| Cyclopentane | None established | 600 ppm |
| 2,2-Dimethylbutane (hexane isomers) | 500 ppm | 500 ppm/1,000 ppm |

mg/m³ milligrams per cubic meter of air volume.
 ppm parts per million
 ACGIH American Conference of Governmental Industrial Hygienists
 OSHA Occupational Safety and Health Administration
 PEL Permissible Exposure Limit
 STEL Short Term Exposure Limit
 TLV Threshold Limit Value
 TWA Time Weighted Average

Concentrations of the blowing agents anticipated incidental to proper handling are expected to be well below those which cause acute inhalation effects and below exposure guidelines.

VENTILATION: If dust is generated indoors and exceeds its PEL, use local exhaust ventilation.

RESPIRATORY PROTECTION: It is good practice to conduct personal monitoring to determine a worker’s potential exposure to airborne concentrations of respirable and/or total dust during handling and use of this product, including activities such as fabrication which generate dust. If concentrations are below applicable exposure limits, respiratory protection is not required. If concentrations exceed the applicable exposure limits and while engineering controls are being implemented, use a NIOSH approved air-purifying respirator equipped with the appropriate filter in accordance with an employer/company-specific Respiratory Protection Program.

EYE AND FACE PROTECTION: Eye protection should not be necessary when handling the board. However, safety glasses with side shields should be worn as minimum protection if fabrication processes are being performed. Dust goggles are recommended to be worn when excessively (visible) dusty conditions are present or anticipated. There is a potential for severe eye irritation if exposed to excessive concentrations of dust for those using contact lenses. An eye wash station should be immediately available at the work area.

SKIN AND FOOT PROTECTION: No precautions necessary.

HAND: Use gloves to protect from mechanical injury as necessary.

PERSONAL HYGIENE: Wash dust-exposed hands with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Avoid breathing dust.

SAFETY DATA SHEET

OX Engineered Products LLC, Charleston, Illinois
11255 North 5th Street
Charleston, IL 61920
800-345-8881

Prepared 9/20/2018



| SECTION 9 | PHYSICAL AND CHEMICAL PROPERTIES |
|---------------------------------------|---|
| Appearance: | Tan Board (an Article as defined by OSHA) |
| Odor and Odor Threshold: | Mild |
| pH: | Not applicable |
| Melting Point/Freezing Point: | Not applicable |
| Boiling Point: | Not applicable |
| Flash Point: | Not applicable |
| Flammability/Explosive Limits: | Not applicable |
| Autoignition Temperature: | 490°C (914°F) ASTM D1929 |
| Vapor Pressure: | Not applicable |
| Vapor Density: | Not applicable |
| Relative Density (water = 1): | 0.25 (estimated) |

| SECTION 10 | STABILITY |
|--|-----------|
| STABILITY: Stable under ambient and anticipated storage and handling conditions. | |
| INCOMPATIBILITY (MATERIALS TO AVOID): None known | |
| CONDITIONS TO AVOID: Avoid temperatures above 150°C (302°F). Exposure to elevated temperatures can cause product to decompose. Avoid direct sunlight. | |
| HAZARDOUS DECOMPOSITION PRODUCTS: Decomposition products will depend on temperature, air supply, and presence of other materials. Toxic gases may be released during decomposition. | |
| HAZARDOUS POLYMERIZATION: Will not occur. | |

| SECTION 11 | TOXICOLOGICAL INFORMATION |
|---|---------------------------|
| PRIMARY ROUTES OF EXPOSURE: Inhalation of dusts. Repeated exposures to dusts of this material are not anticipated to result in systemic toxicity or permanent lung injury; however excessive exposures may cause less severe respiratory effects. Additives are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency. | |
| EYE CONTACT: Fabrication processes may release airborne dust which may irritate eyes. | |
| SKIN CONTACT: Direct contact may cause irritation by mechanical abrasion. | |
| SKIN ABSORPTION: Not known to be a significant route of exposure. | |
| INGESTION: Very low toxicity if swallowed. May cause choking if swallowed. | |

SAFETY DATA SHEET

OX Engineered Products LLC, Charleston, Illinois
1255 North 5th Street
Charleston, IL 61920
800-345-8881

Prepared 9/20/2018



| SECTION 12 | ECOLOGICAL INFORMATION |
|---|------------------------|
| <p>No bioconcentration of the polymeric component is expected. If spilled in the soil, the material is expected to remain in the soil. In the aquatic environment, material is expected to float.</p> <p>No appreciable biodegradation is expected.</p> <p>Not expected to be acutely toxic to aquatic organisms.</p> | |

| SECTION 13 | DISPOSAL CONSIDERATIONS |
|--|-------------------------|
| <p>Dispose of waste materials only in accordance with applicable federal, state, and local regulations. As a supplier of this board, OX Paperboard has no control over the management practices or manufacturing processes of parties handling or using this material. The information presented in this SDS pertains ONLY to the product (an article as defined by OSHA) as shipped in its intended condition. For unused and uncontaminated boards, the preferred options include sending to a licensed, permitted landfill, incinerator, or other thermal destruction device.</p> | |

| SECTION 14 | TRANSPORT INFORMATION |
|---|-----------------------|
| U.S. Department of Transportation (USDOT): | Not regulated |
| Transportation of Dangerous Goods (TDG): | Not regulated |
| IATA Cargo Transport: | Not regulated |
| IATA Passenger Transport: | Not regulated |
| IMDG-Code: | Not regulated |

| SECTION 15 | IDENTIFICATION |
|----------------------------|--|
| CERCLA: | Not regulated |
| TSCA Status: | Not regulated |
| DSL Status: | No substances are specified on any list. No control measures are imposed to any substance contained in this board. |
| SARA 313: | This product contains Aluminum dust, CAS 7429-90-5 less than 5%, which is subject to the reporting requirements. |
| PENN RTK: | U.S. Pennsylvania Worker and Community Right-to-Know Law (34 PA Code Chap. 301-323). |
| California Prop 65: | WARNING: This product contains a chemical(s) (Sulfamic Acid CAS 5329-14-6) known to the State of California to cause cancer, birth defects or other reproductive harm. |

SAFETY DATA SHEET

OX Engineered Products LLC, Charleston, Illinois
1255 North 5th Street
Charleston, IL 61920
800-345-8881

Prepared 9/20/2018



| SECTION 16 | OTHER INFORMATION |
|--|-------------------|
| <p>DISCLAIMER:</p> <p>The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to ensure proper use of these materials and the safety and health of employees. The data in this SDS was prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information to comply with all laws, standards, and regulations applicable to the safe handling and use of these products and to determine the suitability of the product for its intended use.</p> | |